

**Scentinel® A Gas Odorant**

Version 1.3

Revision Date 2011-01-31

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**Product information**

Trade name : Scentinel® A Gas Odorant
Material : 1106807, 1098462, 1102596, 1086453, 1098407, 1086452,
1102264, 1072060, 1098463, 1103512, 1070006, 1024777,
1024776, 1024775, 1024774, 1029441, 1029442, 1029443,
1029444, 1029445

EC-No.Registration number

Chemical Name	CAS-No. Index-No.	Registration number
Ethyl Mercaptan	75-08-1 016-022-00-9	01-2119491286-30-0000

Relevant Identified Uses Supported : Manufacture
Distribution
Use as an intermediate
Formulation
Injection as odorant in fuels – industrial

Company : Chevron Phillips Chemical Company LP
10001 Six Pines Drive
The Woodlands, TX 77380

Local : Chevron Phillips Chemicals International N.V.
Brusselsesteenweg 355
B-3090 Overijse
Belgium

MSDS Requests: (800) 852-5530
Technical Information: (832) 813-4862
Responsible Party: Product Safety Group
Email:msds@cpchem.com

Emergency telephone:**Health:**

866.442.9628 (North America)
1.832.813.4984 (International)

Transport:

North America: CHEMTREC 800.424.9300 or 703.527.3887
Asia: +800 CHEMCALL (+800 2436 2255) China: 0532.8388.9090
EUROPE: BIG +32.14.584545 (phone) or +32.14583516 (telefax)
Chemcare Asia: Tel: +65 6848 9048 - Mob: +65 8382 9188 - Fax: +65 6848
South America SOS-Cotec Inside Brazil: 0800.111.767 Outside Brazil: +55.19.3467.1600

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

Responsible Department : Product Safety and Toxicology Group
 E-mail address : MSDS@CPChem.com
 Website : www.CPChem.com

2. HAZARDS IDENTIFICATION**Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Flammable liquids, Category 1	H224: Extremely flammable liquid and vapor.
Acute toxicity, Category 4	H302: Harmful if swallowed.
Acute toxicity, Category 4	H332: Harmful if inhaled.
Acute aquatic toxicity, Category 1	H400: Very toxic to aquatic life.
Chronic aquatic toxicity, Category 1	H410: Very toxic to aquatic life with long lasting effects.

Classification (67/548/EEC, 1999/45/EC)

Highly flammable	R11: Highly flammable.
Harmful	R20: Harmful by inhalation.
Harmful	R20/22: Harmful by inhalation and if swallowed.
Dangerous for the environment	R50/53: Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Label elements**Labeling (REGULATION (EC) No 1272/2008)**

Hazard pictograms : 

Signal Word : Danger

Hazard Statements : H224 Extremely flammable liquid and vapor.
 H302 Harmful if swallowed.
 H332 Harmful if inhaled.
 H410 Very toxic to aquatic life with long lasting effects.

Precautionary Statements : **Prevention:**
 P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 P233 Keep container tightly closed.
 P240 Ground/bond container and receiving equipment.
 P243 Take precautionary measures against static discharge.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:
 P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
 P304 + P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P312 Call a POISON CENTER or doctor/

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

physician if you feel unwell.

Storage:

P403 + P235

Store in a well-ventilated place. Keep cool.

Disposal:

P501

Dispose of contents/ container to an approved waste disposal plant.

Hazardous ingredients which must be listed on the label:

- 75-08-1 Ethyl Mercaptan

Additional Labeling:

The following percentage of the mixture consists of ingredient(s) with unknown hazards to the aquatic environment: 1 %

The following percentage of the mixture consists of ingredient(s) with unknown acute toxicity: 1 %

3. COMPOSITION/INFORMATION ON INGREDIENTS

Synonyms : Scentinel® A Gas Odorant
 ETSH
 Ethanethiol
 Ethyl Mercaptan

Molecular formula : C₂H₆S
 Index-No. : 016-022-00-9
 EINECS-No. : 200-837-3

Mixtures**Hazardous ingredients**

Chemical Name	CAS-No. EINECS-No.	Classification (67/548/EEC)	Classification (REGULATION (EC) No 1272/2008)	Concentration [wt%]
Ethyl Mercaptan	75-08-1 200-837-3	F; R11 Xn; R20 N; R50-R53	Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Acute Tox. 4; H302 Flam. Liq. 1; H224 Acute Tox. 4; H332	60 - 100

EC-No.Registration number

Chemical Name	CAS-No. EINECS-No.	Registration number
Ethyl Mercaptan	75-08-1 200-837-3	01-2119491286-30-0000

For the full text of the R-phrases mentioned in this Section, see Section 16.

For the full text of the H-Statements mentioned in this Section, see Section 16.

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

4. FIRST AID MEASURES

- General advice : Move out of dangerous area. Consult a physician. Show this material safety data sheet to the doctor in attendance. Symptoms of poisoning may only appear several hours later. Do not leave the victim unattended.
- If inhaled : Call a physician or poison control center immediately. If unconscious place in recovery position and seek medical advice.
- In case of skin contact : If on skin, rinse well with water. If on clothes, remove clothes.
- In case of eye contact : Immediately flush eye(s) with plenty of water. Remove contact lenses. Protect unharmed eye. Keep eye wide open while rinsing. If eye irritation persists, consult a specialist.
- If swallowed : Keep respiratory tract clear. Do NOT induce vomiting. Do not give milk or alcoholic beverages. Never give anything by mouth to an unconscious person. If symptoms persist, call a physician. Take victim immediately to hospital.

5. FIRE-FIGHTING MEASURES

- Flash point : -48 °C (-54 °F)
- Autoignition temperature : 295 °C (563 °F)
- Suitable extinguishing media : Alcohol-resistant foam. Carbon dioxide (CO₂). Dry chemical.
- Unsuitable extinguishing media : High volume water jet.
- Specific hazards during fire fighting : Do not allow run-off from fire fighting to enter drains or water courses.
- Special protective equipment for fire-fighters : Wear self contained breathing apparatus for fire fighting if necessary.
- Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. For safety reasons in case of fire, cans should be stored separately in closed containments. Use a water spray to cool fully closed containers.
- Fire and explosion protection : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.
- Hazardous decomposition products : Carbon oxides. Sulfur oxides.

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

6. ACCIDENTAL RELEASE MEASURES

- Personal precautions : Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapors accumulating to form explosive concentrations. Vapors can accumulate in low areas.
- Environmental precautions : Prevent product from entering drains. Prevent further leakage or spillage if safe to do so. If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods for cleaning up : Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

7. HANDLING AND STORAGE**Handling**

- Advice on safe handling : Avoid formation of aerosol. Do not breathe vapors/dust. Avoid contact with skin and eyes. For personal protection see section 8. Smoking, eating and drinking should be prohibited in the application area. Take precautionary measures against static discharges. Provide sufficient air exchange and/or exhaust in work rooms. Open drum carefully as content may be under pressure. Dispose of rinse water in accordance with local and national regulations.
- Advice on protection against fire and explosion : Do not spray on an open flame or any other incandescent material. Take necessary action to avoid static electricity discharge (which might cause ignition of organic vapors). Use only explosion-proof equipment. Keep away from open flames, hot surfaces and sources of ignition.

Storage

- Requirements for storage areas and containers : Prevent unauthorized access. No smoking. Keep container tightly closed in a dry and well-ventilated place. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Observe label precautions. Electrical installations / working materials must comply with the technological safety standards.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION**Ingredients with workplace control parameters****Chevron Phillips Chemical Company LP**

Ingredients	Basis	Value	Control parameters	Note
Ethyl Mercaptan	Manufacturer	TWA	0,5 ppm,	

LT

Komponentai	Pagrindas, bazė	Vertė	Kontrolės parametrai	Pastaba
Ethyl Mercaptan	LT OEL	IPRD	1 mg/m3	O,

MSDS Number:100000068741

5/24

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

O Oksiduojanti

LV

Sastāvdaļas	Bāze	Vērtība	Pārvaldības parametri	Piezīme
Ethyl Mercaptan	LV OEL	AER 8 st	1 mg/m3	

PL

Składniki	Podstawa	Wartość	Parametry dotyczące kontroli	Uwaga
Ethyl Mercaptan	PL NDS	NDS	1 mg/m3	
	PL NDS	NDSch	2 mg/m3	

PT

Componentes	Bases	Valor	Parâmetros de controlo	Nota
Ethyl Mercaptan	PT OEL	VLE-MP	0,5 ppm,	

SI

Komponente	Osnova	Vrednost	Parametri nadzora	Pripomba
Ethyl Mercaptan	SI OEL	MV	0,5 ppm, 1,3 mg/m3	

SK

Súčasti	Podstata	Hodnota	Kontrolné parametre	Poznámka
Ethyl Mercaptan	SK OEL	NPEL	0,5 ppm, 1,3 mg/m3	Kategórie II,
	SK OEL	CEIL	2,6 mg/m3	Kategórie II,

Kategórie II Faktory so systémovými účinkami. Trvanie piku: 15 minút priemerná hodnota. Frekvencia za zmenu: 4. Interval medzi pikmi: 1hodina. Kategória II znamená, že NPEL môže byť krátkodobo prekročený maximálne 2- 8 krát za zmenu. Maximálne trvanie priemernej pikovej expozície nesmie presiahnuť 15 minút 4-krát za zmenu v intervale jednej hodiny medzi pikmi, pričom priemerný NPEL za 8-hodinovú zmenu musí byť dodržaný.

AT

Inhaltsstoffe	Basis	Wert	Zu überwachende Parameter	Bemerkung
Ethyl Mercaptan	AT OEL	TMW	0,5 ppm, 1 mg/m3	
	AT OEL	KZW	0,5 ppm, 1 mg/m3	

BE

Bestanddelen	Basis	Waarde	Controleparameters	Opmerking
Ethyl Mercaptan	BE OEL	TGG 8 hr	0,5 ppm, 1,3 mg/m3	

DE

Inhaltsstoffe	Basis	Wert	Zu überwachende Parameter	Bemerkung
Ethyl Mercaptan	DE TRGS 900	AGW	0,5 ppm, 1,3 mg/m3	DFG,

DFG Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission)

DK

Komponenter	Basis	Værdi	Kontrolparametre	Note
Ethyl Mercaptan	DK OEL	GV	0,5 ppm, 1 mg/m3	

EE

Komponendid, osad	Alused	Väärtus	Kontrolliparameetrid	Märkused
Ethyl Mercaptan	EE OEL	Piirnorm	0,5 ppm, 1 mg/m3	C,

C Kantserogeensed ained

ES

Componentes	Base	Valor	Parámetros de control	Nota
Ethyl Mercaptan	ES VLA	VLA-ED	0,5 ppm, 1,3 mg/m3	

FI

Aineosat	Peruste	Arvo	Valvontaa koskevat muuttujat	Nota
Ethyl Mercaptan	FI OEL	HTP-arvot 15 min	0,5 ppm, 1,3 mg/m3	°,

° Tarkistettu, ei muutettu

FR

Composants	Base	Valeur	Paramètres de contrôle	Note
Ethyl Mercaptan	FR VLE	VME	0,5 ppm, 1 mg/m3	normal,

normal Valeurs limites indicatives

GB

Ingredients	Basis	Value	Control parameters	Note
Ethyl Mercaptan	GB EH40	TWA	0,5 ppm, 1,3 mg/m3	
	GB EH40	STEL	2 ppm, 5,2 mg/m3	

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

GR

Συστατικά	Βάση	Τιμή	Παράμετροι ελέγχου	Σημείωση
Ethyl Mercaptan	GR OEL	TWA	10 ppm, 25 mg/m ³	
	GR OEL	STEL	10 ppm, 25 mg/m ³	

HU

Komponensek	Bázis	Érték	Ellenőrzési paraméterek	Megjegyzés
Ethyl Mercaptan	HU OEL	AK-érték	1 mg/m ³	i,
	HU OEL	CK-érték	1 mg/m ³	i,

i Ingerlő anyag (izgatja a bőrt, nyálkahártyát, szemet vagy mindhármát)

IE

Ingredients	Basis	Value	Control parameters	Note
Ethyl Mercaptan	IE OEL	OELV - 8 hrs (TWA)	0,5 ppm, 1 mg/m ³	
	IE OEL	OELV - 15 min (STEL)	2 ppm, 3 mg/m ³	

DNEL : End Use: Workers
Routes of exposure: Inhalation
Potential health effects: Chronic effects, Systemic effects
Value: 14,5 mg/m³

DNEL : End Use: Workers
Routes of exposure: Skin contact
Potential health effects: Chronic effects, Systemic effects
Value: 2,06 mg/kg

DNEL : End Use: Workers
Routes of exposure: Inhalation
Potential health effects: Chronic effects, Local effects
Value: 18,6 mg/m³

PNEC : Fresh water
Value: 0,0001 mg/l

PNEC : Marine water
Value: 0,00001 mg/l

PNEC : Fresh water sediment
Value: 0,00049 mg/kg

PNEC : Marine sediment
Value: 0,000049 mg/kg

PNEC : Soil
Value: 0,000039 mg/kg

Personal protective equipment

Respiratory protection : In the case of vapor formation use a respirator with an approved filter.

Hand protection : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Eye wash bottle with pure water. Tightly fitting safety goggles. Wear face-shield and protective suit for abnormal processing problems.

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

Skin and body protection : Impervious clothing. Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : Avoid contact with skin, eyes and clothing. When using do not eat or drink. When using do not smoke. Wash hands before breaks and immediately after handling the product.

For additional details, see the Exposure Scenario in the Annex portion

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties****Appearance**

Form : Liquid

Physical state : Liquid

Color : Colorless

Odor : Repulsive

Safety data

Flash point : -48 °C (-54 °F)

Lower explosion limit : 2,8 %(V)

Upper explosion limit : 18 %(V)

Oxidizing properties : No

Autoignition temperature : 295 °C (563 °F)

Molecular formula : C₂H₆S

Molecular Weight : No data available

pH : Not applicable

Pour point : No data available

Boiling point/boiling range : 35 °C (95 °F)

Vapor pressure : 16,20 PSI
at 37,8 °C (100,0 °F)

Water solubility : Negligible

Partition coefficient: n-octanol/water : No data available

Viscosity, kinematic : No data available

Relative vapor density : 2,1
(Air = 1.0)

Evaporation rate : 1

Percent volatile : > 99 %

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

10. STABILITY AND REACTIVITY**Possibility of hazardous reactions**

- Conditions to avoid : Heat, flames and sparks.
- Materials to avoid : May react with oxygen and strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
- Other data : This material is considered stable under normal ambient and anticipated storage and handling conditions of temperature and pressure.
No decomposition if stored and applied as directed.

11. TOXICOLOGICAL INFORMATION**Acute oral toxicity**

- Ethyl Mercaptan : LD50: 682 mg/kg
Species: rat
Sex: male
Method: Fixed Dose Method

Acute inhalation toxicity

- Ethyl Mercaptan : LC50: > 2,52 mg/l
Exposure time: 4 HR
Species: rat
Sex: male and female
Method: OECD Test Guideline 403

Acute dermal toxicity

- Ethyl Mercaptan : LD50: > 2.000 mg/kg
Species: rat
Sex: male
Method: OECD Test Guideline 402

Scentinel® A Gas Odorant

- Skin irritation : Mild skin irritation

Scentinel® A Gas Odorant

- Eye irritation : Mild eye irritation

Repeated dose toxicity

- Ethyl Mercaptan : Species: rat, Male and female
Sex: Male and female
Application Route: Inhalation
Dose: 0, 25, 100, 400 ppm
Exposure time: 13 wks
Number of exposures: 6 hr/d, 5 d/wk
NOEL: 100 ppm
Lowest observable effect level: 400 ppm

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

Method: OECD Guideline 413
Information given is based on data obtained from similar substances.

Species: rat, Male and female

Sex: Male and female

Application Route: Oral

Dose: 0, 10, 50, 200 mg/kg

Exposure time: 42-53 days

NOEL: 50 mg/kg

Method: OECD Guideline 422

Information given is based on data obtained from similar substances.

Reproductive toxicity

Ethyl Mercaptan : Species: rat
Application Route: Oral diet
Dose: 0, 10, 50, 200 mg/kg
Exposure time: 42-53 days
Number of exposures: once daily
Method: OECD Guideline 422
NOAEL Parent: 200 mg/kg
NOAEL F1: 50 mg/kg

Teratogenicity

Ethyl Mercaptan : Species: rat
Application Route: Inhalation
Dose: 0, 0.037, 0.28, or 0.56 mg/L
Number of exposures: 6 hrs/d
Test period: GD 6-19
Method: OECD Guideline 414
NOAEL Teratogenicity: > 0,56 mg/l

Species: rat
Application Route: Inhalation
Dose: 0, 10, 100, 200 ppm
Number of exposures: 6 hrs/d
Test period: GD 6-19
Method: OECD Guideline 414
NOAEL Teratogenicity: > 200 ppm
NOAEL Maternal: > 200 ppm

Aspiration toxicity

Ethyl Mercaptan : May be harmful if swallowed and enters airways.

CMR effects

Ethyl Mercaptan : Carcinogenicity: Not available
Mutagenicity: Not mutagenic in Ames Test.
Teratogenicity: Animal testing did not show any effects on fetal development.
Reproductive toxicity: Animal testing did not show any effects on fertility.

Scentinel® A Gas Odorant

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

Further information : Solvents may degrease the skin.

12. ECOLOGICAL INFORMATION**Toxicity to fish**

Ethyl Mercaptan : 2,4 mg/l
Exposure time: 96 HR
Species: Oncorhynchus mykiss (rainbow trout)
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates.

Ethyl Mercaptan : EC50: < 0,1 mg/l
Exposure time: 48 HR
Species: Daphnia magna (Water flea)
static test Method: OECD Test Guideline 202

Toxicity to algae

Ethyl Mercaptan : EC50: 3 mg/l
Exposure time: 72 HR
Species: Pseudokirchneriella subcapitata (green algae)
Method: OECD Test Guideline 201

Elimination information (persistence and degradability)

Bioaccumulation : This material is not expected to bioaccumulate.

Biodegradability : This material is not expected to be readily biodegradable.

Further information on ecology**Results of PBT assessment**

Ethyl Mercaptan : Non-classified PBT substance, Non-classified vPvB substance

Additional ecological information : An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Very toxic to aquatic life with long lasting effects.

13. DISPOSAL CONSIDERATIONS

The information in this MSDS pertains only to the product as shipped.

Use material for its intended purpose or recycle if possible. This material, if it must be discarded, may meet the criteria of a hazardous waste as defined by US EPA under RCRA (40 CFR 261) or other State and local regulations. Measurement of certain physical properties and analysis for regulated components may be necessary to make a correct determination. If this material is classified as a hazardous waste, federal law requires disposal at a licensed hazardous waste disposal facility.

Product : The product should not be allowed to enter drains, water

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

courses or the soil. Do not contaminate ponds, waterways or ditches with chemical or used container. Send to a licensed waste management company.

Contaminated packaging : Empty remaining contents. Dispose of as unused product. Do not re-use empty containers. Do not burn, or use a cutting torch on, the empty drum.

For additional details, see the Exposure Scenario in the Annex portion

14. TRANSPORT INFORMATION

The shipping descriptions shown here are for bulk shipments only, and may not apply to shipments in non-bulk packages (see regulatory definition).

Consult the appropriate domestic or international mode-specific and quantity-specific Dangerous Goods Regulations for additional shipping description requirements (e.g., technical name or names, etc.) Therefore, the information shown here, may not always agree with the bill of lading shipping description for the material. Flashpoints for the material may vary slightly between the MSDS and the bill of lading.

IMO / IMDG

UN2363, ETHYL MERCAPTAN, 3, I, MP (ETHYL MERCAPTAN), (-48 °C)

IATA

UN2363, ETHYL MERCAPTAN, 3, I

ADR

UN2363, ETHYL MERCAPTAN, 3, I

RID

UN2363, ETHYL MERCAPTAN, 3, I

15. REGULATORY INFORMATION**National legislation****Chemical Safety Assessment**

Ingredients : ethanethiol A Chemical Safety Assessment 200-837-3 has been carried out for this substance.

Major Accident Hazard : 96/82/EC Update: 2003
Legislation Highly flammable

7b
Quantity 1: 5.000 t
Quantity 2: 50.000 t

: 96/82/EC Update: 2003
Dangerous for the environment
9a
Quantity 1: 100 t
Quantity 2: 200 t

Scentinel® A Gas Odorant

Version 1.3


Revision Date 2011-01-31

Notification status

Europe REACH : On the inventory, or in compliance with the inventory
 United States of America US.TSCA : On the inventory, or in compliance with the inventory
 Canada DSL : On the inventory, or in compliance with the inventory
 Australia AICS : On the inventory, or in compliance with the inventory
 New Zealand NZIoC : On the inventory, or in compliance with the inventory
 Japan ENCS : On the inventory, or in compliance with the inventory
 Korea KECI : On the inventory, or in compliance with the inventory
 Philippines PICCS : On the inventory, or in compliance with the inventory
 China IECSC : On the inventory, or in compliance with the inventory

16. OTHER INFORMATION

NFPA Classification : Health Hazard: 2
 Fire Hazard: 4
 Reactivity Hazard: 0

**Further information**

Legacy MSDS Number : 25580

Significant changes since the last version are highlighted in the margin. This version replaces all previous versions.

The information in this MSDS pertains only to the product as shipped.

The above information is based on the data of which we are aware and is believed to be correct as of the date hereof. Since this information may be applied under conditions beyond our control and with which we may be unfamiliar and since data made available subsequent to the date hereof may suggest modifications of the information, we do not assume any responsibility for the results of its use. This information is furnished upon condition that the person receiving it shall make his own determination of the suitability of the material for his particular purpose.

Key or legend to abbreviations and acronyms used in the safety data sheet

ACGIH	American Conference of Government Industrial Hygienists	LOAEL	Lowest Observed Adverse Effect Level
AICS	Australia, Inventory of Chemical Substances	NFPA	National Fire Protection Agency
DSL	Canada, Domestic Substances List	NIOSH	National Institute for Occupational Safety & Health
NDSL	Canada, Non-Domestic Substances List	NTP	National Toxicology Program
CNS	Central Nervous System	NZIoC	New Zealand Inventory of Chemicals
CAS	Chemical Abstract Service	NOAEL	No Observable Adverse Effect Level
EC50	Effective Concentration	NOEC	No Observed Effect Concentration
EC50	Effective Concentration 50%	OSHA	Occupational Safety & Health Administration
EINECS	European Inventory of Existing Chemical Substances	PEL	Permissible Exposure Limit
MAK	Germany Maximum Concentration Values	PICCS	Philippines Inventory of Commercial Chemical Substances
GHS	Globally Harmonized System	PRNT	Presumed Not Toxic
>=	Greater Than or Equal To	RCRA	Resource Conservation Recovery Act

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

IC50	Inhibition Concentration 50%	STEL	Short-term Exposure Limit
IARC	International Agency for Research on Cancer	SARA	Superfund Amendments and Reauthorization Act.
IECSC	Inventory of Existing Chemical Substances in China	TLV	Threshold Limit Value
ENCS	Japan, Inventory of Existing and New Chemical Substances	TWA	Time Weighted Average
KECI	Korea, Existing Chemical Inventory	TSCA	Toxic Substance Control Act
<=	Less Than or Equal To	UVCB	Unknown or Variable Composition, Complex Reaction Products, and Biological Materials
LC50	Lethal Concentration 50%	WHMIS	Workplace Hazardous Materials Information System
LD50	Lethal Dose 50%		

Full text of R-phrases referred to under sections 2 and 3

R11	Highly flammable.
R20	Harmful by inhalation.
R20/22	Harmful by inhalation and if swallowed.
R50	Very toxic to aquatic organisms.
R50/53	Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
R53	May cause long-term adverse effects in the aquatic environment.

Full text of H-Statements referred to under sections 2 and 3.

H224	Extremely flammable liquid and vapor.
H302	Harmful if swallowed.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

Annex**1. Short title of Exposure Scenario: Manufacture**

Main User Groups	:	SU 3: Industrial uses: Uses of substances as such or in preparations at industrial sites
Sector of use	:	SU3, SU8, SU9: Industrial Manufacturing (all), Manufacture of bulk, large scale chemicals (including petroleum products), Manufacture of fine chemicals
Process category	:	PROC1: Use in closed process, no likelihood of exposure PROC3: Use in closed batch process (synthesis or formulation) PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities PROC15: Use as laboratory reagent
Environmental release category	:	ERC1, ERC4: Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles
Further information	:	Manufacture of the substance or use as a process chemical or extraction agent. Includes recycling/ recovery, material transfers, storage, maintenance and loading (including marine vessel/barge, road/rail car and bulk container), sampling and associated laboratory activities

ERC1, ERC4:**Manufacture of substances, Industrial use of processing aids in processes and products, not becoming part of articles****Environment factors not influenced by risk management**

Flow rate	:	18.000 m3/d
Dilution Factor (River)	:	10
Dilution Factor (Coastal Areas)	:	100

Other given operational conditions affecting environmental exposure

Number of emission days per year	:	365
Emission or Release Factor: Water	:	0 %
Emission or Release Factor: Soil	:	0 %
Remarks	:	Emission or Release Factor: Air : < 0.001 %

Technical conditions and measures / Organizational measures

Air	:	Treat air emission to provide a typical removal efficiency of (%): (Effectiveness: > 99,9 %)
Remarks	:	Wastewater emission controls are not applicable as there is no direct release to wastewater.

Conditions and measures related to municipal sewage treatment plant

Flow rate of sewage treatment plant effluent	:	2.000 m3/d
Remarks	:	Not applicable as there is no release to wastewater.

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC3, PROC8b, PROC15: Use in closed process, no likelihood of exposure, Use in closed batch process (synthesis or formulation), Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent

Amount used

Remarks : Not applicable

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio (PEC/PNEC):
ERC1, ERC4	EUSES		Fresh water		0,0018 µg/L	0,018
			Marine water		0,0001 µg/L	0,015
			Soil		0,0013 µg/kg	0,0379
			Freshwater sediment		0,0039 µg/kg	0,0364
			Marine sediment		0,0003 µg/kg	0,0304
			Air		0,0010 µg/m3	

ERC1: Manufacture of substances

ERC4: Industrial use of processing aids in processes and products, not becoming part of articles

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis.

1. Short title of Exposure Scenario: Distribution

Main User Groups : **SU 3:** Industrial uses: Uses of substances as such or in preparations at industrial sites

Sector of use : **SU3:** Industrial Manufacturing (all)

Process category : **PROC1:** Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
: **PROC8b:** Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC15: Use as laboratory reagent

Environmental release category : **ERC1, ERC2, ERC3, ERC4, ERC5, ERC6a, ERC6b, ERC6c, ERC6d, ERC7:** Manufacture of substances, Formulation of preparations, Formulation in materials, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in inclusion into or onto a matrix, Industrial use resulting in manufacture of another substance (use of intermediates), Industrial use of reactive processing aids, Industrial use of monomers for manufacture of thermoplastics, Industrial use of process regulators for polymerisation processes in production of resins, rubbers, polymers, Industrial use of substances in closed systems

Further information : Loading (including marine vessel/barge, rail/road car and IBC loading) and repacking (including drums and small packs) of substance, including its sampling, storage, unloading distribution and associated laboratory activities.

ERC1, ERC2, ERC3,

ERC4, ERC5, ERC7, ERC6a: Manufacture of substances, Formulation of preparations, Formulation in materials, Industrial use of processing aids in processes and products, not becoming part of articles, Industrial use resulting in inclusion into or onto a matrix, Industrial use of substances in closed systems, Industrial use resulting in manufacture of another substance (use of intermediates)

Environment factors not influenced by risk management

Flow rate : 18.000 m³/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 300
Emission or Release Factor: Air : 0,001 %
Emission or Release Factor: Soil : 0,001 %
Remarks : Emission or Release Factor: Water : < 0.001 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: > 99,9 %)
Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of ≥ (%): (Effectiveness: 99,9 %)
Remarks : Negligible wastewater emissions as process operates without water contact.

Conditions and measures related to municipal sewage treatment plant

Flow rate of sewage treatment plant effluent : 2.000 m³/d
Remarks : Not applicable as there is no release to wastewater.

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4,, PROC8b,, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Transfer of substance or preparation into small containers (dedicated filling line, including weighing), Use as laboratory reagent

Amount used

Remarks : Not applicable

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio (PEC/PNEC):
ERC1	EUSES		Fresh water		0,0029 µg/L	0,0287
			Marine water		0,0007 µg/L	0,0734
			Soil		0,0058 µg/kg	0,169
			Freshwater sediment		0,0062 µg/kg	0,0579
			Marine sediment		0,0016 µg/kg	0,148
			Air		0,0027 µg/m3	

ERC1: Manufacture of substances

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis.

1. Short title of Exposure Scenario: Use as an intermediate

Main User Groups : **SU 3:** Industrial uses: Uses of substances as such or in preparations at industrial sites

Sector of use : **SU 3, SU8, SU9:** Industrial uses: Uses of substances as such or in preparations at industrial sites, Manufacture of bulk, large scale chemicals (including petroleum products), Manufacture of fine chemicals

Process category : **PROC1:** Use in closed process, no likelihood of exposure

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

PROC2: Use in closed, continuous process with occasional controlled exposure

PROC3: Use in closed batch process (synthesis or formulation)

PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises

: **PROC8b:** Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities

PROC8b: Transfer of substance or preparation (charging/discharging) from/ to vessels/ large containers at dedicated facilities

PROC15: Use as laboratory reagent

Environmental release category : **ERC6a:** Industrial use resulting in manufacture of another substance (use of intermediates)

Further information : Use of substance as an intermediate (not related to Strictly Controlled Conditions). Includes recycling/ recovery, material transfers, storage, sampling, associated laboratory activities, maintenance and loading (including marine vessel/barge, road/rail car and bulk container).

ERC6a: Industrial use**resulting in manufacture of another substance (use of intermediates)****Environment factors not influenced by risk management**

Flow rate : 18.000 m³/d
 Dilution Factor (River) : 10
 Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 300
 Emission or Release Factor: Air : 0,01 %
 Emission or Release Factor: Soil : 0,1 %
 Remarks : Emission or Release Factor: Water : < 0.001 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: > 99,9 %)
 Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of ≥ (%): (Effectiveness: 99,9 %)
 Remarks : Negligible wastewater emissions as process operates without water contact.

Conditions and measures related to municipal sewage treatment plant

Remarks : Not applicable as there is no release to wastewater.

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4,, PROC8b, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent

Amount used

Remarks : Not applicable

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio (PEC/PNEC):
ERC6a	EUSES		Freshwater		0,0039 µg/L	0,0393
			Marine water		0,0013 µg/L	0,132
			Soil		0,0116 µg/kg	0,338
			Freshwater sediment		0,0085 µg/kg	0,0794
			Marine sediment		0,0028 µg/kg	0,266
			Air		0,0055 µg/m3	

ERC6a: Industrial use resulting in manufacture of another substance (use of intermediates)

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis.

1. Short title of Exposure Scenario: Formulation

Main User Groups : **SU 3:** Industrial uses: Uses of substances as such or in preparations at industrial sites

Sector of use : **SU 3, SU 10:** Industrial uses: Uses of substances as such or in preparations at industrial sites, Formulation [mixing] of preparations and/ or re-packaging (excluding alloys)

Process category : **PROC1:** Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)
PROC4: Use in batch and other process (synthesis) where opportunity for exposure arises
: PROC 5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact)
: PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

dedicated facilities
PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
: Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
PROC15: Use as laboratory reagent

Environmental release category : **ERC2:** Formulation of preparations
Further information : Formulation, packing and re-packing of the substance and its mixtures in batch or continuous operations, including storage, materials transfers, mixing, tableting, compression, pelletisation, extrusion, large and small scale packing, sampling, maintenance and associated laboratory activities.

ERC2: Formulation of**preparations****Environment factors not influenced by risk management**

Flow rate : 18.000 m³/d
Dilution Factor (River) : 10
Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 365
Emission or Release Factor: Air : 0,025 %
Emission or Release Factor: Soil : 0 %
Remarks : Emission or Release Factor: Water : < 0.001 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%): (Effectiveness: > 99,9 %)
Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of ≥ (%): (Effectiveness: 99,9 %)
Remarks : Soil emission controls are not applicable as there is no direct release to soil.

Conditions and measures related to municipal sewage treatment plant

Remarks : Not applicable as there is no release to wastewater.

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3, PROC4,, PROC8b,, PROC15, PROC26: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), Use in batch and other process (synthesis) where opportunity for exposure arises, PROC 5: Mixing or blending in batch processes for formulation of preparations and articles (multistage and/or significant contact),

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Transfer of substance or preparation into small containers (dedicated filling line, including weighing), Use as laboratory reagent, Handling of solid inorganic substances at ambient temperature

Amount used

Remarks : Not applicable

3. Exposure estimation and reference to its source**Environment**

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio (PEC/PNEC):
ERC2	EUSES		Freshwater		0,0028 µg/L	0,0280
			Marine water		0,0007 µg/L	0,0698
			Soil		0,0124 µg/kg	0,360
			Freshwater sediment		0,0060 µg/kg	0,0566
			Marine sediment		0,0015 µg/kg	0,141
			Air		0,0076 µg/m3	

ERC2: Formulation of preparations

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis.

1. Short title of Exposure Scenario: Injection as odorant in fuels – industrial

Main User Groups : **SU 3:** Industrial uses: Uses of substances as such or in preparations at industrial sites

Sector of use : **SU3:** Industrial Manufacturing (all)

Process category : **PROC1:** Use in closed process, no likelihood of exposure
PROC2: Use in closed, continuous process with occasional controlled exposure
PROC3: Use in closed batch process (synthesis or formulation)
: PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities
PROC8b: Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities
PROC15: Use as laboratory reagent
PROC16: Using material as fuel sources, limited exposure to unburned product to be expected

Environmental release category : **ERC7:** Industrial use of substances in closed systems

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

Further information : Covers injection as odourant in fuel and includes activities associated with its transfer, use, equipment maintenance and handling of waste.

of substances in closed systems**ERC7: Industrial use****Environment factors not influenced by risk management**

Flow rate : 18.000 m³/d
 Dilution Factor (River) : 10
 Dilution Factor (Coastal Areas) : 100

Other given operational conditions affecting environmental exposure

Number of emission days per year : 365
 Emission or Release Factor: Air : 0,025 %
 Emission or Release Factor: Soil : 0 %
 Remarks : Emission or Release Factor: Water : < 0.001 %

Technical conditions and measures / Organizational measures

Air : Treat air emission to provide the required removal efficiency of (%) (Effectiveness: > 99,9 %)
 Water : Treat onsite wastewater (prior to receiving water discharge) to provide the required removal efficiency of ≥ (%): (Effectiveness: 99,9 %)
 Remarks : Soil emission controls are not applicable as there is no direct release to soil.

Conditions and measures related to municipal sewage treatment plant

Remarks : Not applicable as there is no release to wastewater.

Conditions and measures related to external treatment of waste for disposal

Waste treatment : External treatment and disposal of waste should comply with applicable local and/or national regulations.

Conditions and measures related to external recovery of waste

Recovery Methods : External recovery and recycling of waste should comply with applicable local and/or national regulations.

2.2 Contributing scenario controlling worker exposure for: PROC1, PROC2, PROC3,, PROC8b, PROC15: Use in closed process, no likelihood of exposure, Use in closed, continuous process with occasional controlled exposure, Use in closed batch process (synthesis or formulation), PROC8b: Transfer of substance or preparation (charging/discharging) from/to vessels/large containers at dedicated facilities, Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at dedicated facilities, Use as laboratory reagent

Amount used

Remarks : Not applicable

3. Exposure estimation and reference to its source

Scentinel® A Gas Odorant

Version 1.3

Revision Date 2011-01-31

Environment

Contributing Scenario	Exposure Assessment Method	Specific conditions	Compartment	Value type	Level of Exposure	Risk characterization ratio (PEC/PNEC):
ERC7	EUSES		Fresh water		0,0028 µg/L	0,0280
			Marine water		0,0007 µg/L	0,0698
			Soil		0,0124 µg/kg	0,360
			Freshwater sediment		0,0060 µg/kg	0,0566
			Marine sediment		0,0015 µg/kg	0,141
			Air		0,0076 µg/m3	

ERC7: Industrial use of substances in closed systems

4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the Exposure Scenario

RMMs and OCs are described in adequate documentation at site level and efficiency is checked on a regular basis.